Simplicity Slimline/ Utility



Multiboost Simplicity Slimline/ Utility: 350L, 450L (Vario)

The Multiboost Simplicity 350L / 450L is the first entry level system in the Multiboost Range. It has been designed to fit through a standard doorway. This makes it very convenient for new or existing properties as it can be easily fitted under a stairs or in a utility room. The slimline range is ideal for 3 - 5 bedroom houses, with poor water pressure and flow and where floor space is limited.

Key Features

- 3 piece union on outlet (for easy maintenance for crimp piping)
- > 16 amp rated controller with pressure gauge as standard
- Non-corrosive holding tank (WRAS approved material)
- > Start up pressure adjustable from 0.8 to 2.5 bar
- Minimal installation requirement
- > Dry run protection on controller
- Overflow fitted (as standard)
- Auto restart (4 attempts)
- > Drain-off plug



Range Options

Product Code	Model				
1031919	350L Simplicity Slimline (Vario)				
1033476	450L Simplicity Utility (Vario)				

System Connections

Connection	Size
Inlet*	½″BSP
Outlet	1"BSP
Overflow	1" BSP
Drain Off	1"BSP

^{*}Bypass unit recommended to be fitted on inlet supply Available Drip Tray is recommended to be used on installation





	Fixed Speed Option						
Power supply	240 volt, 50Hz						
Pump	Pedrollo TOP Multi 2 (240 volt)						
Controller	Presflo (16 amp)						
Current Input	3.4 amp						
Mains Power Cable	5mtr x 1.5mm ² 3 core						
Pump dB Rating (approx.)	<65dB						
Tank Weight Empty	350L = 29kg	450L = 35kg					
Tank Weight Full	1L of water = 1 kg plus weight of empty tank						
Access Cover Ø	300L = 195mm 500L = 285mm						

Adjustable cut-in feature from 0.8 to 2.5 bar Pressure gauge





Vario Controller

Dumm Tum a	Po	ver O.V.:	30	40	50	60	70	80				
Pump Type	kW	НР	Q I/min	0	10	20	30	40	50	60	70	80
Top Multi 2	0.55	0.75	H Metres	42	40	38	34	30	24	18	11.5	5